



HEAVY DUTY PEAK PERFORMANCE

318 mm / 12.52"



645 mm / 25.39"

Depth
328 mm / 12.91"




Technical Information

Airwatts	750
Suction	146" H ₂ O
Airflow	141.2 CFM
Noise Level	65 dB
Canister	22L / 5.81 Gal.
Motor Size	5.7" / 145 mm
Motor Type	Thru-Flow
Motor Fan	2-stage
Motor SKU	MOT-392
PC Board SKU	6114-19HF2
Soft-Start/Stop	Yes
Bottom Load	Yes
Depth	328 mm / 12.91"
Height	645 mm / 25.39"
Width	318 mm / 12.52"

HYBRID CYCLONIC FILTRATION With or without a disposable filtration bag

Wall mounting
bracket
MUSUP-V4



Disposable filtration
bags (3-pack)
12.5L / 3.2 Gal.
FD-12.5L-3NAD



Mandatory
permanent filter
(Machine washable)
FP-8

Special Features

PEERLESS PERFORMANCE MOTOR



Soft-start / stop
technology

LED INDICATOR



Displays the status of the
unit and a reminder to
empty the canister

HYBRID CYCLONIC FILTRATION



Can be used with or
without a disposable
filtration bag

BOTTOM LOAD CANISTER



Easy removal
wherever it's installed

POLISHED ALUMINUM



Impeccable
standards

- ✓ RUSTPROOF
- ✓ LIGHTWEIGHT
- ✓ SMOOTH AND SHINY

NADAIR®

Since 1980

SIMPLIFIED LIFE!

NASP-HD750-22H-EN-11-04-2024